

Control pedestal for offshore

U23 / 23



The control pedestal U23 / 23 accommodates the devices necessary for control and monitoring.
Ready wired, it can be quickly and easily installed on the sea deck. The housing (pedestal head) is made of seawater-resistant aluminium.

Surface treatment:

Priming and structur-finishing paint

Standard colour RAL 7032 pebble-grey

Technical data:

Operation temperature	-40°C to +60°C
Degree of protection	IP66



Example

		U23 / 23	/	N61.../N62...	/	H / PW / 2D	/	PQ	/	KLV	/	X
Housing												
U23/23	with 1 narrow side-plate with pillar-gasket											
U23/23A	Side-plate narrow gasket											
IA	Monitoring devices cover with gasket for max. 2 monitors 72x72 mm or 4 monitors 72x36mm and max. 6 indicating devices pos. 28, 29											
RS	Pillar 108mm Ø 670mm height with flange quadratic or round											
Masterswitch / Control-switch												
N61	HG Masterswitch with ball handle and indicating labels											
N62	KN Control-switch with knob and indicating label											
		- HG	- 01 Z P	- A05	P134	- X						
Axis 1: direction 3-4												
		(Standard contacts gold-plated 2A 250V AC15)										
01	2 contacts	Standard contact - arrangement see page 112										
02	4 contacts	z.B.										
03	6 contacts	A05	MS21									
04	8 contacts	A0500	MS21-00									
		<i>A99 contact - arrangement according customer request</i>										
Z	Spring return											
R	Friction brake											
P	Potentiometer	P131	T396 2x0,5kOhm	I max. 1mA								
		P132	T396 2x1kOhm	I max. 1mA								
		P133	T396 2x2kOhm	I max. 1mA								
		P134	T396 2x5kOhm	I max. 1mA								
		P135	T396 2x10kOhm	I max. 1mA								
		<i>More potentiometer on request!</i>										

U23 / 23 / N61.../N62... / H / PW / 2D / PQ / KLV / X

Command and indicating devices		
H	Heating	20 Watt 220 or 110V 50/60 Hz
PV	Mushroom head push button latching	22 latching with indicating label 1 NC
P	Mushroom head push button	22 with indicating label 1 NO
D	Push button	22 with indicating label 1 NO
W	Selector switch 0--1	22 with indicating label 1 NO
L	Indicator light	22 with indicating label Diode 24 Volt
L	Indicator light	22 with indicating label Diode 230 Volt AC
	Contact block additional	1S or 1Ö
L	Indicator light	22 with indicating label Diode 24 Volt protection IP65
L	Indicator light	10 with indicating label Diode 24 Volt protection IP65
Display devices		
PQ	Powermeter PQ 72 1mA DC	Engraved your instructions
PQI	Powermeter PQ 72 1mA DC illuminated 24 Volt	Engraved your instructions
PQ	Powermeter PQ 72x36 1mA DC	Engraved your instructions
PQI	Powermeter PQ 72x36 1mA DC illuminated 24 Volt	Engraved your instructions
EQ	Amperemeter EQ 72 100/200/1A	Engraved your instructions
EQI	Amperemeter EQ 72 100/200/1A illuminated 24 Volt	Engraved your instructions
EQ	Amperemeter EQ 72x36 100/200/1A	Engraved your instructions
EQI	Amperemeter EQ 72x36 100/200/1A illuminated 24 Volt	Engraved your instructions
Wiring		
KLV on terminal block 2,5qmm with wire line 0,75qmm		
Special model		
X	Special / customer-specific	

3

