

**MFS100 Microphone Flow Switch**

Approximate shipping weight: 6 lbs / 2.7 kg

Model **MFS100**

**STANDARD FEATURES:**

- sensor - strap-on acoustic
- sensor cable - 5ft / 1.5m shielded coaxial
- enclosure - watertight NEMA4X (IP67) fiberglass
- 1 relay - 5 amp SPDT
- indication - power and relay condition LED's
- sensitivity - adjustable
- power input - 120VAC 50/60Hz
- 1 Manual - Installation and Operation

OPTIONS	STOCK NO.	
<b>POWER INPUT</b>		
220VAC 50 Hz	EI	
24VDC	24VDC	
<b>STAINLESS STEEL SENSOR MOUNTING CLAMPS</b>		
1½ - 72 in (38 - 1800 mm) ID pipe	PC3	
<b>OTHERS</b>		
Replacement sensor with 5 ft / 1.5m cable	MSE	
Spare/Replacement Electronics with mounting plate	CHS	
Extra sensor cable up to 20 ft / 6m	XC	
Enclosure Heater and Thermostat (15 watts)	TH	
Conformal Coating (PC boards coated to seal out moisture, "tropicalized")	CFS	
Additional Manuals (1 supplied with each unit)	MNL	

Standardowa dostawa : 3-4 tygodnie (+ 10% dla RUSH - przyspieszona dostawa 2-3 tygodnie)

**PRODUCENT** Greyline Instruments Inc

**DYSTRYBUCJA w Polsce**

**Elektro-Trading Sp. z o.o.**

**44-109 Gliwice , ul. Mechaników 9**

**Tel: 032 734-55-72**

**Tel/Fax : 032 734-55-70**

[www.elektro-trading.com.pl](http://www.elektro-trading.com.pl)

[et@elektro-trading.com.pl](mailto:et@elektro-trading.com.pl)