

Why "shoot" at hot spots one shot at a time with an IRgun, when you can scan them with rapidatoratic "fire"?

The palm-size Microscanner "E" and "Super-E" models are the infrared scanners which scan electrical equipment faster, safer and with more accuracy than "point and shoot" guns, because they are designed from the "ground up" for rapid electrical scanning - like using a machine gun instead of a pistol. Because of outstanding speed and color-coded display, the "E" models can scan twenty panels in the same time it takes to scan one panel with a conventional IR gun. Because of the higher optical resolution, scanning can be from farther away, thus improving safety for the professional.



Distributed By

ELEKTRO-TRADING sp. z o.o.

44-109 Gliwice, ul.P. Gojawiczynskiej 13 Tel. +48 (0-32) 330-45-70, 734-55-72 Fax. +48 (0-32) 330-45-74, 734-55-70 www.elektro-trading.com.pl e-mail: info@elektro-trading.com.pl



51 Water Street
Watertown, MA 02172
617-923-9900
800-422-3006
FAX 617-923-9911
The invertors of hard-held electrical IR scaning.



for Electrical Professionals.



IR.1PROEE




Microscamer E



Microscarner SLERE with Laser

Plug-in Infrared Probe for Digital Multimeters




The PROBE requires no batteries, can be carried in your tool kit wherever you go, and requires only a little more IR.1PROBE Plugged Into DMM space

than your regular voltage probes. With a minimum spot size of 0.2 in (5 mm), you can Circuit. inspect the smallest **Roards** chips, splices, and clips. You can even plug the PROBE into your oscilloscope!

Stran

Small Size Fits Any Toolbox. Low Cost Fits Any Budget.



IR.1PROBE

Field-of-view	1:1		
Output signal	0.1 mV/°C (Temperature rise above probe temperature)*		
Accuracy**	1°C (lifetime calibration)		
Target Distance	up to 3 in (8 cm)		
Minimum Spot	0.2 in (0.5 cm)		
Range	-50 to 1200°F (-46 to 650°C)		
Operating	-50 to 175°F (-46 to 80°C)		
Response time	0.1 second (not including DMM)		
Power requirement	None		
Construction	Impact resistant, hermetically sealed, intrinsically safe		
One-handed operation	Clips to standard probe holder		
Price			
* for insulator targets up to approximately 100 °C rise			

- for insulator targets up to approximately 100 °C rise. For higher temperatures, refer to manual.
- @ 25°C ambient, 35°C 0.9 emissivity target, meter error not included.

Selection of the correct IR Scanner depends primarily on the distance to the targets to be scanned. The following recommendations can be used to select the optimum model:

Scanning Distance Recommended	Model
up to 3 in (7.5 cm)	IR.1PROBE
up to 12 ft (4 m)	Microscanner E
up to 50 ft (15 m)	Microscanner Super E

For heavy duty scanning, the Micro E and Super E are the models of choice for electrical professionals because the inspection can be performed **more** accurately, in less time, and more safely than with infrared "guns". The table below compares the E models to a typical gun model, which shows why the E models are the IR scanners of choice for serious electrical professionals.

	Microsc Super E	IR Gun*	
Field-of-View (max)	200:1	50 :1	30:1
Maximum Distance for 1 in (2.5 cm) spot	17 ft (5 m)	4 ft (1.3 m)	2.5 ft (0.8 m)
Scan Readings/sec	20	10	1** to 4
Time to Scan 1 x 4 ft (.3 x 1.3 m) Panel @ Distance	<30secs @17 ft	<60secs @4 ft	2.5 to 10 mins @2.5 ft
	(5 m)	(1.3 m)	(0.8 m)
Resolution	0.1°C	1°C	1°C
Automatic Ambient	yes	yes	no
Scanning Display/ Thermal Patterns	yes	yes	no
Color-coded Scale	yes	yes	no
Locking Display	yes	no	yes
Peak Hold Display	yes	no	no
Audible Heat Seeker	yes	no	no
Waterproof Case	yes	no	no
Weight	7 oz (200 g)	6 oz (170 g)	20 oz (600 g)
Warranty	3 years	1 year	1 year
Price			
Optional Laser Sight			
* Typical conventional in	fraged gup		

- Typical conventional infrared gun
- ** Est. time to read display